

KND312/525



Sniper Rifle Scope

#DaySight



HIGH PERFORMANCE OPTICS
GRADUAL ILLUMINATED RETICLE
RETICLE FOCAL PLANE: 1

aselsansivas

www.aselsansivas.com

KND312/525

Sniper Rifle Scope

Mastery over distance requires an optical system that translates ballistic variables into absolute certainty. The KND312 / KND525 sniper rifle scopes are engineered for elite marksmen who operate in the high-stakes environments of modern reconnaissance and precision engagement. Designed to eliminate the margin of error, these systems offer a fluid mechanical interface and superior light transmission to ensure that every long-range kinetic decision is backed by uncompromising visual data.

The hallmark of the KND series is its continuous zoom capability, allowing for smooth target tracking and identification across varying magnification ranges. By utilizing a first focal plane (FFP) reticle architecture, the subtensions remain constant regardless of magnification, enabling instantaneous ranging and holdovers without complex recalibration. Complementing this is a gradual illuminated reticle, which provides the operator with precise contrast control, ensuring the point of aim is visible against complex backgrounds or in the fading light of dusk and dawn.

General Specifications

Ballistic Precision: Features a First Focal Plane (FFP) reticle with continuous zoom and gradual illumination for rapid ranging and target engagement at all magnification levels.

Operational Resilience: Fully certified to MIL-STD-810G standards, maintaining peak performance from -30°C to +55°C with 1-meter submersible water resistance.

Modular Architecture: Designed with a standardized Picatinny interface and supports secondary mission-specific attachments like reflex sights and anti-reflection honeycomb filters.



Technical Specifications

• Magnification	: 3X-12X / 5X-25X
• Aperture	: 50 mm / 56 mm
• Field of View	: 11 m-3.4 m / 5.3 m-1.5 m
• Parallax Adjustment	: From 50m / 25m to infinity
• Eye Relief	: 80 mm / 85 mm
• Wind./Ele. Adjustment	: 1 cm @ 100 m
• Total Reticle	: Windage :±60 clicks : Elevation: 240 clicks
• Double Turn Indicator	: Yes
• Reticle	: Mil-Dot
• Reticle Focal Plane	: 1st Focal Plane
• Reticle Illumination	: 11 Levels
• Diopter	: 3/+2
• Battery	: CR2032
• Weight	: 900 gr / 1100gr
• Length	: 380 mm / 430 mm



Specifications are subject to change without any notice. | All tolerances are within ±10%.